


All bathtub dimensions are $\pm 1/2"$.

Airbath System II

Blower must be remotely located

(Diagram is required for custom blower connection locations)



LEGEND:



BLOWER OUTLET



REMOTE CONTROL (INVISIBLE MAGNETIC HOLDER)

STANDARD EQUIPMENT:

- Americh Remote Control (with Airbath System only)
- Integral Waste & Overflow with Polished Chrome trim

Available with polished brass, polished nickel, satin nickel or oil rubbed bronze trim at no additional charge if specified at the time of order. Requests after order is shipped are subject to a \$75 list charge for trim

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Airbath III units may be $1\frac{1}{2}"$ - $2\frac{1}{2}"$ higher than stated.
- Any whirlpool or Airbath® unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
- Always consult your local plumber for recommendations as installations will vary.

DIMENSIONS:

71" x 35" x 25" (1083 x 889 x 635 mm)

Gallon to Overflow = 85 (Liters = 322)

MATERIAL: Acrylic (All Americh Standard Colors)

TUB FLOOR: Non-Textured

UNDERMOUNT: No

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

OPTIONAL ACCESSORIES

- Chromatherapy
- Pillows: 13"

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- ANSI Z124.1

Contact Americh for additional approvals.