

PREP KITCHEN FAUCET


Features

- Solid brass construction
- High-arc 360° rotating spout allows for easy filling of large pots and cleaning
- Magnetic docking secures sprayhead into spout
- One button brass sprayhead has dual function aerated or spray mode
- Spray jets have easy-to-clean surface that withstand mineral build-up
- Quiet polymer-braided hose with rotating joint at sprayhead allows for smooth and non-binding use
- Ceramic disc cartridge
- 1.8 gpm (6.8 L/min) max flow rate Over 30 finishes including 15 PVD finishes

Codes/Standards Applicable

Meets or exceeds the following at date of manufacture:
• ASME A112.18.1/CSA B125.1

- NSF 61 and NSF 372



DIMENSIONS (in.)					THROUGH-HOLE SPECIFICATIONS
XX HANDLE	Α	В	С		MIN RECOMENDED MAX ∅1-1/4" ∅1-3/8" ∅1-3/8"
33	7 1 2	4 1/8	3 13 16		Ψ1-1/4 Ψ1-3/6 Ψ1-3/6
35	7 1 2	4 1 8	3 13 16	 	7 ³ / ₄ "
40	7 1 4	4	3 5 8		
42	7 1	3 <mark>15</mark>	3 9 16		
55	7 1 4	4	3 5 8		
64	7 7 16	4 1 6	$3\frac{7}{8}$		
CLEV	7 9 16	4 3 16	3 15 16	В —	- 5 15 "
		1 9 16 (WITH S	PACER)	9 7 16" 4 3 8	
	(2 1/4" M (LESS SP.)	IAX ACER)	$3\frac{7}{16}"$ $2\frac{1}{8}"$	$2\frac{1}{4}$ " -1 $17\frac{7}{8}$ " $17\frac{7}{8}$ "
				3/8" CON FITTING	IPRESSION IN THE PROPERTY OF T