





<u>60" [1524mm] Shower</u> <u>w/8 1/2" [216mm] Threshold, Molded Seat,</u> <u>& Molded Soap Ledges</u>

CENTER DRAIN
Left Hand Version (5836LX/S) Shown

## PRODUCT SPECIFICATIONS:

- \* Certified to meet CSA B45.5/IAPMO Z124 Standard.
- \* Product has a Class B fire rating as determined by ASTM E-84 test method.
- \* Reinforced & slip resistant floor.
- \* Integral 1" [25mm] nailing flange.
- \* Molded soap ledges on three walls.
- \* Molded seat approx. 13"W x 20"D x 22 1/2"H (opposite of valve wall).
- \* Door Opening: W-57" [1448mm]

H-69 1/2" [1765mm]

- \* Accepts Clarion Bathware Model IN60C cap (adds 6" [152mm] to the overall height of the unit)
- \* All dimensions +/- 1/2" [12.8mm]
- \* Clarion Bathware reserves the right to change design and/or dimensions.
- \* Dimensions are the same for RE, MP, and all other versions of this model.

## 5836LX/S or 5836RX/S

60" [1524mm] Shower w/ 8 1/2" [216mm] Threshold, Molded Seat, Molded Soap Ledges, & Center Drain

Clarion
BATHWARE
44 Amsler Ave.
Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228

Fax: (814) 226-0730 www.clarionbathware.com

3	Signatures For A Customer: Arch./Engr:	Approval:	Date:	Dwg. # 5836LX/S or RX/S-CUT
n	Quote #: Job Name:			Dwg. By: CAL DATE: 5/3/2021