



*** For clarity, ***
the whirlpool piping
has been omitted
from this drawing

PRODUCT SPECIFICATIONS:

- * Certified to meet CSA B45.5/IAPMO Z124 Standard.
- * Product has a Class B fire rating as determined by ASTM E-84 test method.
- * When installing this whirlpool, an access area should be provided near the location of the whirlpool pump for future access. An access area is required by many local, state & federal building codes.
- * Recommended access area dimensions: W-20" [508mm] H-15" [381mm]
- * Reinforced & slip resistant floor.
- * Integral 1" [25mm] nailing flange.
- * Factory drilled 2 1/2" [64mm] overflow.
- * Molded shelving on the back wall of the unit.
- * Door Opening: W-56 7/8" [1445mm] H-57 3/4" [1467mm]
- * Bathwell Dimensions (At Top): W-55" [1397mm]

D-21 1/2" [546mm]

H-14 1/4" [362mm]

Dwg. # RE7933L or R

-4&6 JETCUT

Dwg. By: CAL

DATE: 5/11/2021

- * Bathwell Dimensions (At Bottom): W-46" [1168mm] D-19" [483mm]
- * Bathwell Capacity (At Overflow): 44 Gal [167L]
- * Water Level (At Overflow): 10 1/4" [260mm]
- * Accepts Clarion Bathware Model 931 Cap. (Adds 9" [229mm] to the overall height of the unit)
- * In a 6 jet system the pump will stick out 3" from the rough-in dimensions.
- * All dimensions +/- 1/2" [12.8mm]
- * Clarion Bathware reserves the right to change design and/or dimensions.
- * Dimensions are the same for RE, MP, and all other versions of this model.

Additional Jets For 6 Jet Systems On/Off 123 [324mm] Suction Jets for 4 & 6 Jet Systems On/Off Air Control PLAN ON [1524mm] A PLAN ON [1524mm]

60" [1524mm] Tub/Shower w/ Molded Shelving & 4 or 6 Jet Whirlpool Package

Left Hand Version (RE7933L:4 or RE7933L:6) Shown

RE7933L:4, RE7933L:6, RE7933R:4, or RE7933R:6

60" [1524mm] Tub/Shower w/ Molded Shelving & 4 or 6 Jet Whirlpool Package

BATHWARE 44 Amsler Ave. Shippenville, PA 16254

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com

Signatures For Approval:

Customer:
Arch./Engr:

Quote #:
Job Name: