


ELEVATION

SECTION "A-A"

PRODUCT SPECIFICATIONS:

- Product material AcrylixTM surface with fiberglass composite reinforcement.
- Certified to meet CSA B45.5/IAPMO Z124 Standard.
- This unit can be reinforced to meet the accessibility requirements for Type B dwellings upon request.
- When installing this whirlpool, an access area should be provided near the location of the whirlpool pump for future access. An access area is required by many local, state & federal building codes.
- Recommended access area dimensions: W-20" [508mm] x H-15" [381mm]
- When properly accessorized and installed, product meets requirements of ADA (2010 Std), ICC/ANSI A117.1-2017, ABA or UFAS.
- Product has a Class B fire rating as determined by ASTM E-84 test method.
- Sufficient drain clearance to accommodate above the floor plumbing.
- Reinforced & slip resistant floor.
- Integral 1" [25mm] nailing flange.
- Factory drilled 2 1/2" [64mm] overflow.
- Door Opening: W-56" [1422mm] x H-58" [1473mm]
- Bathwell Dimensions (At Top): W-53" [1346mm] x D-21 3/4" [552mm] x H-13 1/2" [343mm]
- Bathwell Dimensions (At Bottom): W-43" [1092mm] x D-18 1/4" [464mm]
- Bathwell Capacity (At Overflow): 36 Gal [136L]
- Water Level (At Overflow): 9 3/4" [248mm]
- On a 6 jet system the pump will stick out up to 3" from the rough-in dimensions.
- All dimensions +/- 1/2" [12.8mm]
- Clarion Bathware reserves the right to change design and/or dimensions.
- Dimensions are the same for RE, MP, and all other versions of this model.



Left Hand Version (RE8011LSDX:4 or RE8011LSDX:6) Shown

RE8011LSDX:4 or RE8011LSDX:6 or or RE8011RSDX:4 or RE8011RSDX:6

59 3/4" [1518mm] Tiled Tub/Shower w/ 18-1/2" [470mm] Apron, Molded Soap Ledges, & Left or Right Hand Drain

BATHWARE 44 Amsler Ave. Shippenville, PA 16254

Air Control-

Phone: (814) 226-5374 Toll Free: (800) 576-9228 Fax: (814) 226-0730 www.clarionbathware.com