





▲ Designate Proper Finish Suffix



see what Delta can do

STEAM CONTROL AND HEAD

Contemporary Round

STEAM CONTROL FEATURES:

- Programmable time and temperature
- Temperature range 60°F min to 125°F max
- Time programmable up to 60 minutes
- Digital display of ambient temperature, set temperature, and elapsed time
- 2 User presets
- Patented Dual Sensor Technology: The control features dual temperature sensors that deliver extremely accurate temperature precision to smoothly regulate the steam shower environment

STEAM CONTROL STANDARD SPECIFICATIONS:

- Surface Mount 1 1/2" hole required
- · Must mount inside the steam room
- The multi-conductor cable should be run through 3/4" conduit to protect cable from damage and to facilitate easy replacement.
- Mount control near seating area and not above Steam head.
- Control should be mounted 48" above the floor
- Required Electrical Service: Low-voltage connection from 5GE-SMP series generators via multiconductor cable (supplied with steam generator)
- Model is not compatible with 5SP-MU-3 audio accessory

STEAMHEAD STANDARD SPECIFICATIONS:

- Includes 3/4" NPT female thread for connection to steam line
- Steam line should protrude 1/4" to 1/2" from finshed surface
- Steam head should be mounted 12" 18" above the finished floor or 6" above the rim of the tub. The mounting location must also not be directly beneath the control and should be as far from the seating area as possible.
- · Includes silicone cover
- Essential oil reserve on top of steam head

WARRANTY

• See separate warranty document