

Wall to Floor w/Outrigger - right & left

*wingit compatible

Configuration: 15-16

Grab Bar

Twist-Lock Concealed

Application Use:

Architectural

Commercial

Institutional

Residential

Specifications

Wall to Floor Safety Bar with outrigger and snap on / twist-lock concealed flanges. Manufactured by ELCOMA from 18 gauge, type 304 stainless steel, satin finished, tubing. 14 gauge stainless steel mounting flanges, heliarc welded to the tube to form a single structural unit. ELCOMA grab bars are designed, built, and tested to withstand 250lbs. (113kgs) of load when properly installed.* This exceeds HUD, FHA, VA, VA, ADA, ANSI and other federal, provincial, and local codes. *Grab Bars can only be as strong as what they are mounted to. It is imperative when installing any safety product to consult with a qualified contractor to insure you have sufficient backing.

Configuration #15 (right hand) shown



Custom sizes are available to suit special requirements.

The exclusive ELCOMA concealed flange system adapts both "Twist-Lock" and "Snap-On" compatibilities making installation a breeze. ELCOMA Wall to Floor Bars come in 1.25" & 1.5" Diameters with a variety of finishes & coatings.

| | |
|--------------------|--|
| Bar Diameter: | 1.25" , & 1.5" |
| Bar Grip: | Smooth, Peened, Knurled, Shur-Grip (available in 1.25" only) |
| Standard Flange: | Twist-Lock / Snap-On concealed * Wingit compatible |
| Optional Flanges: | Bolt, Exposed, & Female Thread Insert |
| Standard Finishes: | Satin Finish, White or Almond Powder Coating |
| Custom Finishes: | Multiple colors & finishes available, call your representative or visit www.elcoma.com for selection grid. |
| Configurations: | Standard: 33"x30" |

