

SPECIFICATION SHEET

Lighted Medicine Cabinet




FEATURES/TYPICAL SPECIFICATIONS

- Surface Mount Installation
 - Pre-drilled mounting holes
- Formed and welded steel housing (WB/ST)
 - 24 gauge steel construction with white, heat cured, acrylic paint finish
- Framed mirror door
 - 2MM thick float glass mirror door front
 - Polished stainless steel frame with tab and screw closure (SS8)
 - 24 gauge steel door back with white, heat cured, acrylic paint finish
- 16" piano hinge welded to the door and mechanically fastened to the cabinet body (HG01) (1 typical)
- Magnetic catch in cabinet body flange aligns to stainless steel striker plate on the door (1 typical)
- Right-hand door swing
- Incandescent dual socket top light with plastic shade. Light box has bright stainless trim strips on both sides. (Uses two 60 watt maximum, medium base, 120V bulbs (I60A) - bulbs not included)
- Grounded convenience outlet and on/off switch located at top of cabinet on right side
- High-impact polystyrene shelves (2 typical)
 - Fixed shelves removable (FX2)
- Includes installation hardware
- Pallet Quantity = 24 units

		Dimensions In Inches					
Model #	Description	Α	В	С	D	Е	F
555IL	MEDCAB 1DR 16X24 SS8 WB/ST	16	24	8	9¾	13¾	51⁄8

REFERENCE	QTY.	REMARKS	Project		
			Location		
			Architect		
			Engineer		
			Contractor		
			Submitted by	Date	

* All models and material specifications are subject to change or withdrawal without notice.



Finishes:

Housing: PT01-Basic White

В