

SPECIFICATION SHEET

Barrington MEDICINE CABINET



FEATURES/TYPICAL SPECIFICATIONS

- Recess or Surface Mount Installation
 - Wall Opening/Rough-in Dimensions (for recess applications):14" x 18" x 3¹/₂"
 - Pre-drilled mounting holes spacing: 11.81" center-tocenter (width) and 15.95 center-to-center (length)
- Formed and welded steel housing (WB/SS)
 - 26 gauge stainless steel
 - 3MM thick float glass mirror with polished edges on housing back
- Framed mirror door
 - Extruded polystyrene frame with laminate, decorative foil in satin nickel finish
 - 1/8" float glass mirror door front with clean cut edges
 - 26 gauge stainless steel door back
- 16" stainless steel piano hinge welded to the door and mechanically fastened to the cabinet body (HG01) (1 typical)
- Round magnet with soft plastic black cover located in the door aligns to the cabinet body flange (1 typical)
- · Reversible for left-hand or right-hand door swing
- 5/32" thick float glass shelves, adjustable (ADJ) (2 typical)
- Includes 3MM thick polished mirror strips to attach to external cabinet side walls for surface mount application (2 typical)
- Mounting hardware included
- Standard Pallet Quantity of 42 units

e:	NI4—Satin Nickel		
		 }	ر ۲
	11/		
	/	в	H
			₽
L		C	
		D -	-

Housing: SS4 - Brushed Stainless Steel

Flat Mirror

Finishes:

Mirror:

Frame:

		Dimensions In Inches									
Model #	Description	Α	В	С	D	Е	F	G	Н	J	к
56SS184CSN	MEDCAB 1DR 15X19 NI4 WB/SS	15	19	1½	5	13½	5⁄8	14¾	17½	5⁄8	1⁄8

	1	1		1		
REFERENCE	QTY.		REMARKS	Project		
				Location		
				Architect		
				Engineer		
				Contractor		
				Submitted by	Date]

* All models and material specifications are subject to change or withdrawal without notice.