

11.5T8/LED/48-830/BP 120-277V	

Notes

General	
Status	Active
Watts	11.5
Fluorescent Equivalent	32
Volts	120V-277V
Ballast Type	Туре В
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	80
Lumens	1650
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120- 277V line voltage; No ballast or external driver required
Dimming Type	N/A
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical	
MOL	48
MOD	1
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.85

Additional Information		
Additional Info	Installation protection - will not light if ballast is not bypassed.	
Shatter-Proof Type	PET Coated	
Installation Notes	Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring	
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass	
Compliance		
Safety Listing	cULus Classified	

For More Information Visit: https://www.satco.com/

Location Rating

Energy Star



Damp No







DLC Approved	Yes
DLC ID	PL5CBTPA2PS9
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)







