

Project Name

Location Prepared By



Status	Active
Watts	13.5
Volts	120V
Ballast Type	Type B
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	1700
Beam Spread	220
Dimmable	Yes Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120V line voltage; No ballast or externa driver required
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)
Physical	
MOL	48
MOD	1
Lens Finish	Frosted
Lens Material	Glass
Housing Color	White
Additional Information	
Additional Info	All alass tubo

Housing Color	vvriite
Additional Information	
Additional Info	All glass tube
Tube Guard Use	Approved for use with tube guards
Installation Notes	Install only in non-shunted lampholders
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass
Compliance	
Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLV12B1YBIYP
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
FCC Compliant	Yes









NSF Approved

Yes - Approved





