## SATCO' NUVO

Project Name

Location

Prepared By



**SATCO S8605** 

6.5MR16/LED/40'/30K/12V

Notes

| General  |  |
|--|--|
| Status   | Active   |
| Watts  | 6.5  |
| Incandescent Equivalent  | 50   |
| Volts  | 12V  |
| Shape  | MR16   |
| ANSI Base  | GU5.3  |
| Finish   | Silver Back  |
| CCT (Kelvin)   | 3000   |
| Temperature  | Warm White   |
| CRI  | 80   |
| Lumens   | 500  |
| Beam Spread  | 40   |
| Dimmable   | Yes Dimmable   |
| Hours Rated  | 25000  |
| Lamp Type  | MR   |
| Technology   | LED  |
| Electrical   |  |
|  |  |
| Candlepower  | 1060   |
| Candlepower<br>Power Factor  | 1060<br>0.93   |
| •  |  |
| Power Factor   | 0.93<br>-25C (-13F) to a maximum of +45C   |
| Power Factor<br>Operating Temperature  | 0.93<br>-25C (-13F) to a maximum of +45C   |
| Power Factor<br>Operating Temperature<br>Physical  | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)  |
| Power Factor<br>Operating Temperature<br>Physical<br>MOL   | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78  |
| Power Factor<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Additional Information  | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78  |
| Power Factor<br>Operating Temperature<br>Physical<br>MOL<br>MOD  | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2   |
| Power Factor<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Additional Information<br>Enclosure Rating  | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp  |
| Power Factor Operating Temperature Physical MOL MOD Additional Information Enclosure Rating Warranty   | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp  |
| Power Factor<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Additional Information<br>Enclosure Rating<br>Warranty<br>Compliance  | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp<br>5 Year Limited - 10 hr per day                        |
| Power Factor         Operating Temperature         Physical         MOL         MOD         Additional Information         Enclosure Rating         Warranty         Compliance         Safety Listing   | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp<br>5 Year Limited - 10 hr per day<br>CULus               |
| Power Factor         Operating Temperature         Physical         MOL         MOD         Additional Information         Enclosure Rating         Warranty         Compliance         Safety Listing         Location Rating                     | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp<br>5 Year Limited - 10 hr per day<br>cULus<br>Damp       |
| Power Factor         Operating Temperature         Physical         MOL         MOD         Additional Information         Enclosure Rating         Warranty         Compliance         Safety Listing         Location Rating         Energy Star | 0.93<br>-25C (-13F) to a maximum of +45C<br>(+113F)<br>1.78<br>2<br>Enclosed Rated Lamp<br>5 Year Limited - 10 hr per day<br>CULus<br>Damp<br>No |

For More Information Visit: <u>https://www.satco.com/</u>

