

Project Name

Location

Prepared By



Notes

**General**

Status	Active
Watts	13
Fluorescent Equivalent	28; 32
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3000
Temperature	Warm White
CRI	83
Lumens	1800
Beam Spread	240
Dimmable	Non-Dimmable in Bypass Mode
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast required (Type A) or Ballast bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.96
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

**Physical**

MOL	48
MOD	1
Housing Color	White

**Additional Information**

Additional Info	Do not use with dimmers in by-pass mode. Check the ballast for dimming capability when using with a ballast.
Shatter-Proof Type	PET Coated
Specification Note	Ballast Compatible - bare lamp is 12W; Ballast Bypass - 13W.   Protection from arcing- Power must be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracked or electrically compromised. If arcing occurs at the l
Warranty	5 Year Limited - T8 LED Bulbs

**Compliance**

Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp

Energy Star	No
DLC Approved	Yes
DLC ID	PL20BPLJYLDH
CEC Status	Lawful for sale in California
RoHS Compliant	Yes
NSF Approved	Yes - Approved

