



Swanstone Bath Wall Single Panels


WARRANTY
Limited Lifetime – Residential
Limited 30-year – Commercial

Manufactured from Swanstone solid surface
(See page 2 for detailed information.)

Recommended for high-use traffic areas and commercial surfaces.

FEATURES

- Reinforced solid surface means color and texture run all the way through and cannot wear away.
- Will not mold or mildew, no grout to clean.
- Ideal for remodeling, panels glue up over existing surface.
- Coordinates with other Swanstone bath products.
- Can be easily trimmed to fit any shower application.
- Widest range of sizes to fit most any project.
- Heat resistant—walls can handle steamer units.
- Compression molding means superior durability.



Single Panel Shower Walls

- 36" wide x 72" high (914 mm x 1829 mm)
- 60" wide x 72" high (1524 mm x 1829 mm)
- 36" wide x 96" high (914 mm x 2438 mm)
- 48" wide x 96" high (1219 mm x 2438 mm)
- 62" wide x 96" high (1574 mm x 2438 mm)

SPECIFICATIONS

Swanstone Bath Wall Single Panels

Model	Part	Nominal Dimensions	Ship Wt. Lb.	Ship FedEx	Carton Dims. In.	Cu. Ft.
SS-3672-1	SS0367201	36" W x 72" H	53	–	74 x 45 x 4	7.71
SS-6072-1	SS0607201	60" W x 72" H	117	–	78 x 66 x 4	9.29
SS-3696-1	SS0369601	36" W x 96" H	84	–	98 x 38 x 4	8.62
SS-4896-1	SS0489601	48" W x 96" H	96	–	98 x 56 x 4	12.75
SS-6296-1	SS0629601	62" W x 96" H	108	–	102 x 68 x 4	16.06

Kit Includes: One flat wall panel. It may be necessary to combine cartons to accommodate desired installation area. No installation materials provided. Order one **SS-72** installation kit per panel, except for 48" panel, which needs two kits per panel.

Packaging: Each kit is packed in an individual carton.

ACCESSORIES

See page 36 for complete listing of all wall accessories.

STANDARDS AND RATINGS

American Society of Testing and Materials (ASTM) E-84: Class A Flame Spread Rating

American National Standard Institute—ANSI Z124.6

International Association of Plumbing and Mechanical Officials (IAPMO)—Listed

cUPC listed—Certified to CSA Test Standard B45.5 by IAPMO

Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

COLORS

Solid Colors:

- White (010)
- Bisque (018)
- Bone (037)

Aggregate Colors:

- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Canyon (124)
- Cloud Bone (126)
- Cloud White (125)
- Glacier (121)
- Golden Steppe (128)
- Gray Granite (042)
- Ice (130)
- Mountain Haze (129)

- Night Sky (012)
- Pebble (072)
- Prairie (122)
- Tahiti Desert (050)
- Tahiti Gray (053)
- Tahiti Ivory (059)
- Tahiti Matrix (058)
- Tahiti Sand (051)
- Tahiti White (011)
- Tundra (131)

Our Planet Colors

MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and rinse within five minutes of application. Occasional scrubbing with abrasive cleaners ensures that the original luster will be maintained. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. **Do not** use cleaning agents that caution use on acrylic, polyester or plastics.