

Aquia® IV Close Coupled Toilet, 1.28 & 0.8 GPF with WASHLET®+ S500e

FEATURES

- Concealed supply connection for seamless installation
- DynaMax™ Tornado Flush® utilizes 360° cleaning power to reach every part of the bowl
- Ultra high-efficiency dual flush 1.28 & 0.8 GPF (4.8 & 3.0 LPF)
- CeFiONtect® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Design of the bowl reduces water flow resistance resulting in a quieter flushing sound
- Completely skirted design for a sleek and understated look that's easier to clean
- Elongated front bowl, WASHLET and tank set
- Chrome push-button
- 12" Rough-in
- On-demand wand cleaning with ewater+®

MODELS

- MW4463046CEMG (#01)
With CeFiONtect ceramic glaze & WASHLET S500e with contemporary design

COMPONENTS

- CT446CUGT40
Elongated bowl with CeFiONtect
- ST446EM
Tank and cover only
- SW3046T40
WASHLET® S500e with contemporary design
- 9AU321-A
WASHLET adapter

Optional Components

- TSU08W.10
10" Unifit Rough-In
- TSU08W.14
14" Unifit Rough-In

COLORS/FINISHES

- #01 Cotton



 **DynaMax
Tornado Flush**

 **ewater+**

 **CeFiONtect**

 **Skirted Design**

PRODUCT SPECIFICATION

The two-piece, ultra high-efficiency, DynaMax Tornado Flush toilet shall be dual flush 1.28 GPF/0.8 GPF. Toilet shall be coated with CeFiONtect, elongated front bowl, high profile tank, complete skirted bowl and chrome push-button. Toilet shall be TOTO Model MW4463046CEMG#01.

See SW3046T40 Specification Sheet for details on included WASHLET.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others



MW4463046CEMG

Aquia® IV Close Coupled Toilet, 1.28 & 0.8 GPF with WASHLET®+ S500e

SPECIFICATIONS


| | |
|----------------------------|---|
| Water Use | 1.28 & 0.8 GPF (4.8 & 3.0 LPF) |
| Flush System | DynaMax™ Tornado Flush™ |
| Min. Water Pressure | 8 psi (Flowing) |
| Water Surface | 5-5/8" x 4-1/8" |
| Trap Diameter | 2-1/2" |
| Rough-in | 12" (10" & 14" Optional) |
| Trap Seal | 2-1/8" |
| Warranty | One Year Limited Warranty |
| Material | Vitreous China |
| Shipping Weight | CT446CUGT40 85 lbs ST446EM 29 lbs |
| Shipping Dimensions | CT446CUGT40 30-3/4" L x 17-3/8" W x 20-1/2" H ST446EM 17-1/4" L x 7-7/8" W x 17-1/2" H |

See SW3046T40 Specification Sheet for details on included WASHLET.

INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

DIMENSIONS



TOTO®

These dimensions and specifications are subject to change without notice

Ph: (888) 295-8134 | Fax: (800) 699-4889 | www.totousa.com | © TOTO USA

SS-01324 v.02