

Auto Sensor TOTO Soap Dispenser with Subtank

FEATURES

- Sensor operated foaming soap dispenser
- Self-adjusting sensor spout with base unit, mounting hardware and supply lines
- Chrome plated
- Single-hole mount
- TOTO Soap required
- Refillable tank system
- ADA compliant

MODELS

- **2 SPOUT**
TLK03001G#CP (Spout) (Must Purchase 2 Units)
TLK01106U (Controller & Reservoir)
TLK01401U (5.3 gal/20L Subtank)
- **3 SPOUT**
TLK03001G#CP (Spout) (Must Purchase 3 Units)
TLK01107U (Controller & Reservoir)
TLK01401U (5.3 gal/20L Subtank)

COLORS/FINISHES

- #CP Polished Chrome

OPTIONAL ACCESSORY

- THP3140#CP
Escutcheon 1-1/8" ~1-1/2" (28mm~38mm)



Auto Functions

PRODUCT SPECIFICATION

TOTO® Model No. _____
Product shall be automatic infrared sensor activated. Product shall have automatic sensor adjustment upon installation. Soap dispenser, controller w/ reservoir and subtank will be sold separately. Product shall have a controller pump with 0.8 gallon (3L) reservoir. Product shall have a 5.3 gallon (20L) subtank

CODES/STANDARDS

- Meets and exceeds UL1951, CSA C22.2 #68
- Certifications: UL
- Code Compliance: NEC, CEC
- ADA Compliant



TOTO SOAP *(Sold Separately)*

Product No.	Quantity	Packaging	Notes
TSFG1	4 gallons	Package of 4, 1 gal. each	Antimicrobial Soap (Fragrance Free)
TSFG5	5 gallons	Packaged as 1, 5 gal. container	Antimicrobial Soap (Fragrance Free)
TSFG55	55gallons	Packaged as 1, 55 gal. drum	Antimicrobial Soap (Fragrance Free)
TSFB1-GS	4 gallons	Package of 4, 1 gal. each	TOTO Foam Soap Green Seal™ (Lilac)
TSFB5-GS	5 gallons	Packaged as 1, 5 gal. container	TOTO Foam Soap Green Seal (Lilac)



TLK03001G & TLK01106/7U

Auto Sensor TOTO Soap Dispenser with Subtank

SPECIFICATIONS


Power Supply	AC 120V
Wattage	(TLK01106U) 6.5W (TLK01107U) 9W
Sensor Detection Range	5-1/8" ~ 7-7/8" (130~200mm) Sensor is self-adjusting
Ambient Temperature	34-104°F(1-40°C)
Humidity	Max. 90% RH
Power Cord Length	55" (1.4 m)
Soap Output Volume	0.04 oz (factory setting)
Tank Capacity	Approximately 0.8 gal (3L) Tank Approximately 5.3 gal (20L) Subtank
Warranty	*Three Year Warranty

*Failure to use TOTO soap will void warranty

INSTALLATION NOTES

- Spout Mounting Hole $\phi 1"$ ~ $\phi 1\text{-}1/8"$ ($\phi 25$ ~ $\phi 28$ mm)
- Deck Thickness $1/4"$ ~ $1\text{-}1/8"$ (5 ~ 30 mm)

DIMENSIONS



TOTO

These dimensions and specifications are subject to change without notice