

Features

- · Solid brass body
- · Ceramic disk cartridge
- Single lever handle.
- 180 degree swivel spout
- Installation in a 1-3/8" hole
- 1-1/2" maximum deck thickness
- High arc spout with pull-out spray head
- Single function pull-out spray head aerated spray
- Magnetic docking keeps the pull-out spray head firmly in place with an integrated magnet, so it stays docked when not in use.
- 1.8 gpm max. (6.8L/min) @ 60psi saves 20% more water
- Flexible supply lines with 3/8" compression fittings

Optional Accessories

• T3600 soap dispenser.

Specified Model

Warranty

- Lifetime Limited Warranty for residential use
- 5 Year Limited Warranty for commercial use

Model	T3530
Faucet Height	16%4" (410 mm)
Spout Reach	8½" (216 mm)
Deck to Aerator	9 ⁴⁹ ⁄ ₆₄ " (248 mm)
Flow Rate	1.8 gpm max (6.8L/min) @ 60 psi
Shipping Weight	9 lbs.
Material	brass construction
Installation	deck mount, single hole

To Be Specified:

Finish
PC Polished Chrome
LS Luxe Stainless

Codes/Standards

Certified to CUPC Certified to AB1953 Certified to NSF/ANSI 61 Complies with Federal Lead Plumbing Law as certified with IAMPO R&T inc. ADA complaint for lever handle



Notes

Install this product according to the installation instructions.

Single Lever Pull-Out Spray RETREAT T3530



